

<b>Turntable section</b>	
Belt-drive (External drive)	Type
DC Motor	Motor
33- $\frac{1}{2}$ rpm, 45 rpm	Rotation Speeds
0.1% or less	Wow-and-Flutters
67dB (A-weighted, 20kHz LPF)	S/N Ratio
<b>Turntable (Platter)</b>	
Aluminum Die-cast	Material
30cm	Diameter
<b>Tone-arm section</b>	
S-shape, Static-balanced	Type
223mm	Effective Length
0g to 5.0g	Needle Pressure Range
3.0g to 12.0g	Compatible Cartridge Weight
14g to 23g (including Head-shell)	
<b>Cartridge section</b>	
MM-type	Type
4.0mV (1kHz, 5cm/sec.)	Output Voltage
1.8 to 2.2g (2.0g recommended)	Needle Pressure
6.1g	Weight
11g (including screws, nuts, and wires)	Head-shell weight
AT-VMN95E * Average stylus life: approx. 300 hours.	Compatible Stylus
<b>Analog Outputs</b>	
RCA Pin jack $\times$ 1 pair (Gold-plated)	Connector
<b>Output Voltage</b>	
4.0mV (1kHz)	PHONO
224mV (-13dBV)	LINE
AC 100 to 240V, 50/60Hz	Operating Power
1.5W	Power Consumption
0.5W	Standby Power
420 $\times$ 117 $\times$ 356 mm /	Overall Dimensions (W $\times$ H $\times$ D)
16.5" $\times$ 4.6" $\times$ 14.0" (including protrusions)	
approx. 5.0kg / 11.0 lbs.	Weight
Felt Mat, EP Adapter, Counter Weight, Head-shell (AT-VMN95E installed), Platter, Dust Cover, Hinges $\times$ 2, RCA Audio cable with GND terminal, AC Adapter (GPE053A-V120050), Owner's Manual (including Warranty Card)	Included Accessories