

Turntable section	
Direct Drive	Type
Brush-less DC Motor	Motor
33- $\frac{1}{3}$ rpm, 45 rpm	Rotation Speeds
0.10%	Wow-and-Flutters
67dB or higher (A-weighted, 20kHz LPF)	S/N Ratio
Turntable (Platter)	
Aluminium Die-cast	Material
30cm	Diameter
Tone-arm section	
S-shaped, Static-balanced	Type
223mm	Effective Length
0g to 5.0g	Needle Pressure Range
3.0g to 12.0g	Compatible Cartridge Weight
14g to 23g (including Head-shell)	
Head-shell and Cartridge sections	
MM-type (SUMIKO Oyster factory installed)	Type
4.0mV (1kHz)	Output Voltage
1.5 to 2.5g (appropriate value: 2.3g)	Needle Pressure
5.3g	Weight
11g (including nuts, screws, and wires)	Head-shell weight
Styluses for SUMIKO Oyster	Compatible Stylus
Analog Outputs	
RCA Pin jack \times 1 pair (PHONO/LINE switchable Connector)	
Output Voltage	
4.0mV (1kHz)	PHONO
224mV (-13dBV)	LINE
AC 100 to 240V, 50/60Hz	Operating Power
2W	Power Consumption
0.5W or less	Standby Power
420 \times 117 \times 356 mm / 16.5" \times 4.6" \times 14.0"	Overall Dimensions (W \times H \times D)
Approx. 6.1kg / 13.5 lbs.	Weight
Felt Mat, EP Adapter, Counter Weight, Head-shell (SUMIKO Oyster installed), Platter, Dust Cover, Hinges \times 2, RCA Audio cable with GND terminal, AC Adapter (GPE036W-24015), Owner's Manual (including Warranty Card)	Included Accessories